

<b>IC-F2721D</b>	<b>25 Watt, 256 channel capability Mobile Transceiver, comes in 2-tone, 5-tone, CTCSS, DTCS and DTMF encoder and decoder as standard. HM148 Hand-Mic as supplied</b>
<b>IC-F2721D-L</b>	<b>UHF 400-470MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2721D-H</b>	<b>UHF 450-512MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F1821D/2821D</b>	<b>256 channel capability Mobile Transceiver, comes in 2-tone, 5-tone, CTCSS, DTCS and DTMF encoder and decoder as standard. HM148 Hand-Mic with 10 Keypad &amp; SP22 speaker as supplied</b>
<b>IC-F1821D</b>	<b>VHF 50 Watt, 36-174MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2821D-L</b>	<b>UHF 45 Watt, 400-470MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2821D-H</b>	<b>UHF 45 Watt, 450-512MHz, 12.5/25kHz Channel spacing</b>

#### **Microphones**

HM152	Microphone (Non Keypad)
HM152T	DTMF microphone
HM148	Heavy duty microphone (non keypad)
SM25	Desk Microphone, Monitor Switches

#### **Data Cables**

OPC-617	External Modem Connection Cable
---------	---------------------------------

#### **Voice Privacy Options**

UT109#02	Scrambler Frequency Inversion Type
UT110#02	Scrambler Rolling Code Type
UT111	LTR Trunking Unit
100	Option Fitting Fee

#### **External Speakers**

SP22	External Speaker
------	------------------

#### **Programming Equipment**

CS-F1700	Dealer Programming Software
OPC-1122	RS232 Programming Cable
OPC-1122U	USB Programming Cable
500	Programming Fee

#### **Separation Kits for Remote Installation**

RMK2	Separation Kit (Req OPC-607, OPC-608 or OPC-609)
OPC-607	Cable: separation (3m)
OPC-608	Cable: separation (8m)
OPC-609	Cable: separation (1.9m)

#### **Digital Up-grade / Encryption Software (For IC-F2821D/F2821D-L/F2821D-H ONLY)**

UT120#02	DSP Unit for IC-F1710/F2710
FS70/F1700	Flash Loader
EX2785J01	P25 Activation Key, (Required for UT120 Up-grade)
EX2785J02	DES Activation Key, (Digital Option)
EX2785J03	AES Activation Key, (Digital Option)
OPC-1534	Key Loader Cable, IC-F1710/F2710

NOTE: The APCO P25 Standard mandates the Motorola KVL-3000 key Loader Device to load  
The OPC-1534 Cable provides the Inter-face connection between the KVL-3000 Loader & the Icom  
(This strategy is employed to keep security in the field to a maximum at all times)