IC-FR5300/FR6300	VHF and UHF Digital Repeaters
Channel Modules	
UR-FR5300	136-174 MHz, 50/25 W- 25W output power depending on the channel module version
UR-FR6300	400-470, 450-512, 330-400MHZ, 50/25W- 25W output power depending on the channel module version
IDAS Network/Controller Board and Software	
UC-FR5300	Network/controller board. Software (CF card) may be supplied dpeening on UC-FR5300 version
CF-FR5300SC	Simulcast softweare. Same as supplied with UC-FR5300 #14
CF-FR5000MC	Multi-site conventional software. Same as supplied with UC-FR5300 #12
CF-FR5000MT	Multi-site trunking software. Same as supplied with UC-FR5300 #13
GNSS Antenna	
UX-241	External GNSS antenna. Cable length 5m, 16.4 ft.
External Speakers	
SP-35	Compact external speaker- length: 2M 6.6 ft.
SP35L	Compact external speaker- length 6m, 19.7 ft.
Hand Microphone and Desktop Microphone	
HM-152	Hand microphone (for base station operation)
SM-26	Desktop Microphone with Monitor and Monitor lock buttons (for base station operation)
RoIP Gateway	
Non Gateway	

VE-PG4

RoIP gateway. Provides an interconnection with an IP phone, LTE radio, Wlan radio or analog radio