

9/29 14:30

E

FUNC



IP ADVANCED RADIO SYSTEM

LTE Transceiver

LTE (4G) and 3G

Push-to-Talk Instant Communications Communication throughout the Coverage Area of LTE (4G) and 3G Network Talk and Listen Simultaneously: Full-Duplex Conversation

Instant Wide Area Coverage Over a LTE (4G) and 3G Network

The IP501H provides wide area communication using a LTE (4G) and 3G network and instantaneous communication. Individual calls, Group calls or All calls can be made the same way as a conventional two-way radio.

Communication throughout the Coverage of LTE (4G) and 3G Network

LTE (4G) and 3G Network

Using a LTE (4G) and 3G network, the IP501H can provide stable connection and wide area communication throughout the coverage of the network. The IP501H does not require its own repeaters or IP network which reduces the cost of building and maintaining a wide area radio network. * Service availability depends on the country. Network coverage provided by custom ICOM SIM card.



o ICOM

 \triangle

 ∇

IP ADVANCED FADIO SYSTEM IP501H

IP ADVANCED RADIO SYSTEM

IP501H

Cim

FUNC

CLR

Actual Size

.1 880

TG001

m

Ē

9/29 14:30

Security

Event Management

Full-Duplex Communication

The IP501H enables use of full-duplex communication which provides smooth telephone style conversations. The IP501H users can talk and receive at the same time.

Multiple User Communication

Multiple users in the system can initiate calls respectively. There are no requirements to check or wait for channel availability.

Priority Interrupt Calling

The IP501H supports group calls with three or more people. In case of an emergency, you can break into an on-going call to transmit an important message.



Industry Leading Compact and Lightweight Body

Compact $59 \times 95 \times 32$ mm; $2.3 \times 3.7 \times 1.3$ in and 240 g; 8.5 oz (approximate) lightweight body* allows non-intrusive mobility and use. * With BP-272 battery pack and antenna. Projections are not included.

1P67 Dust-Tight and Waterproof

The IP501H has reputable waterproof performance to endure 1 m depth water for 30 minutes. It can be used for outdoor work or places prone to get wet.



Optional Charger Cradle With Bluetooth® Function

When the optional BC-218, charger cradle and HM-215, speaker-microphone is used, calls can be made with the microphone, while charging the IP501H. Even when the IP501H is not dropped into the BC-218, the Bluetooth[®] function enables you to wirelessly use the speaker-microphone.



 * May not be available in some countries. Please confirm the regulations in your country before you use.

Other Features

- High quality, clear audio using G.726 Vocoder
- Individual, Group, Talkgroup, Multiplex Talkgroup and All calls
- Emergency button, Lone Worker and Man Down functions
- Vibration alert function notifies of incoming call
- Text message reception and preprogrammed message transmission
- Up to 500 memory address book (including Group, Individual, Talkgroup and Telephone lists)
- Voice message recording
- Built-in Bluetooth[®] and GPS*

* Gateway device required for GPS data (future).

Interconnect between IDAS[™] and IP100H systems

With a gateway device*, the IP501H system will provide interoperability with an IP phone, analogue transceiver, IDAS[™] digital transceiver and IP100H wireless LAN network systems in the future. In addition, GPS position data can be obtained from the IP501H transceiver.

* The gateway device will be available in the future.





IP ADVANCED RADIO SYSTEM

IP501H

CD-231

For 12 V DC

CIGARETTE LIGHTER CABLES

(for use with BC-218)

With DC-DC converter

EARPHONE-MICROPHONES

CP-22

(12-24 V DC)



*2 OPC-2359 is required when using HS-102

HS-94*3

Earhook type

*3 Either OPC-2006LS or OPC-2328 is required when using any of these headsets. (Simplex mode operation only.)

Behind-the-head type

HS-97*

Throat-microphone type

HS-95*3

SPECIFICATIONS

HS-102*2

Earphone type

| Network | 4G bands: | LTE B1, B3, B7, B8, B20 (EXP) LTE B2, B4, B5, B17 (USA) |
|--|-------------|--|
| | 3G bands: | W-CDMA B1, B8 (EXP) W-CDMA B2, B5 (USA) |
| Dimensions $(W \times H \times D; Projections not included)$ | | 59 × 95 × 32 mm; 2.3 × 3.7 × 1.3 in (with BP-272) |
| Weight (approx.) | | 240 g; 8.5 oz (with BP-272 and antenna) |
| Voice Codec | | G.726 (32 kbps) |
| AF output power | Internal SP | 400 mW (16 Ω at 10% distortion) |
| | External SP | 200 mW (8 Ω at 10% distortion) |
| Operating time* (5:5:90 duty cycle.) | | More than 17 hours (with BP-272) |
| Bluetooth | | Ver 2.1 +EDR |
| GPS | | Built-in |
| Operating temperature | | -10 °C to +60 °C; +14 °F to +140 °F |
| IP rating | | IP67/55/54 |

Applicable U.S. Military Specifications

LC-183*4

For use with BP-271

LC-185*4

*4 Charging is possible while the case is attached.

For use with BP-272

| MIL 810G Standard | Method | Procedure | | |
|--|--------|-----------|--|--|
| Low Pressure | 500.5 | I, II | | |
| High Temperature | 501.5 | I, II | | |
| Low Temperature | 502.5 | I, II | | |
| Temperature Shock | 503.5 | I-C | | |
| Solar Radiation | 505.5 | I | | |
| Rain Blowing/Drip | 506.5 | I, III | | |
| Dust Blowing | 510.5 | I | | |
| Immersion | 512.5 | I | | |
| Vibration | 514.6 | Ι | | |
| Shock | 516.6 | I, IV | | |
| Also meets equivalent MIL-STD-810-C, -D, -E and -F. | | | | |
| Supplied accessories • BP-272 Livion battery pack • MB-135 belt clip | | | | |

Antenna

* Operating time may differ depending on operating environments. All stated specifications are subject to change without notice or obligation.

Please ask your lcom distributor in your country about the planned launch date of the service or other requirements. This product requires the system construction working in collaboration with a mobile network operator. lcom, lcom lnc. and the lcom logo are registered trademarks of lcom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries. IDAS is a trademark of lcom Incorporated. The Bluetooth® word mark and logos are registered trademark owned by Bluetooth SIG, lnc. and any use of such marks by lcom lnc. is under license. All other trademarks are the properties of their respective holders.

| ICOM INC. | 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 | www.icom.co.jp/world |
|-----------|--|----------------------|
|-----------|--|----------------------|

Icom America Inc.

12421 Willows Road NE, Kirkland, WA 98034, U.S.A. Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17A, Delta, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-50 E-mail: info@icomeurope.com URL: http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 E-mail: icom@icomspain.com URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 E-mail: icom@icom-france.com UBL: bth//uwawi.icom_france.com URL: http://www.icom-france.com

Hand strap

VS-3

Bluetooth® headset

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road, Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 E-mail: sales@icom.net.au URL: http://www.icom.net.au Fax:

Shanghai Icom Ltd.

No.101, Building 9, Caifuxingyuan Park, No.188 Maoting Road, Chedun Town, Songjiang District, Shanghai, 201611, China Phone: +86 (021) 6153 2768 Fax: +86 (021) 5755 9987 E-mail: bjicom @bjicom.com URL: http://www.bjicom.com

Your local distributor/dealer:

Count on us!

HM-153LS HM-166LS

• MB-135: Belt clip. Same as supplied.

• OPC-2006LS: Plug adapter cable

• OPC-2328:

PTT switch cable. Either OPC-2006LS or OPC-2328 is required when using any of HS-94, HS-95 or HS-97.

• OPC-2359: PTT switch cable. OPC-2359 is required when using HS-102.